




seguridad eléctrica

BTI, Alfombras dieléctricas para media tensión, clase 0 a clase 4, fabricadas de acuerdo a IEC61111.

Alfombra aislante para protección temporal. Utilizadas en trabajos sin tensión como protección adicional contra descargas o contactos accidentales con partes con tensión. Fabricadas en caucho, haciéndolas más livianas y flexibles. Poseen ambas caras antideslizante, y marcadas en la cara superior para indicar al operario que esta seguro, sobre una alfombra aislante. Disponibles en alfombras de 1x1 m. o en rollos de 1x10 m.




Clase	Tensión máxima de uso	Color de etiqueta
0	1000 V.	Rojo
2	17.000 V.	Amarillo
3	26.500 V.	Verde
4	36.000 V.	Naranja




Superficie anti-deslizante


CLASE 0




CLASE 2



CLASE 3



CLASE 4



CODIGO	CLASE	DIMENSIONES [m.]	PESO [Kg.]	ESPESOR [mm.]	TENSION DE PRUEBA [kVAC.]	TENSION RESISTIDA [kVAC.]	TENSION RECOMENDADA DE USO [kVAC.]
BTIC011	0	1,0 x 1,0	3,4	3,0	5,0	10,0	1,0
BTIR010		10,0 x 1,0	34,0				
BTIC021	2	1,0 x 1,0	3,4	3,0	20,0	30,0	17,0
BTIR0210		10,0 x 1,0	34,0				
BTIC031	3	1,0 x 1,0	4,6	3,0	30,0	40,0	26,5
BTIR0310		10,0 x 1,0	46,0				
BTIC041	4	1,0 x 1,0	6,1	4,0	40,0	50,0	36,0
BTIR0410		10,0 x 1,0	61,0				



TYRSCO S.A. – 25 de Mayo 2666, El Talar (1618), Buenos Aires, Argentina. “LA SEGURIDAD NO ES CUESTION DE SUERTE”
 (+5411) 3221-0729, 4736-7531 - tyrco@tyrco.com.ar - www.tyrco.com.ar




TYRSCO® BTI, Insulated blanket for medium voltage, class 0 to class 4, manufactured under IEC61111.

Insulated blanket for temporary protection. Used in dead line working as additional protection against accidental contact with discharges or live parts. Made of rubber, making them lighter and more flexible. Antislip surface on both sides, and marked on the upper face to indicate to the operator that it is safe, on an insulating blanket. Available in sheets of 1x1 m. or in rolls of 1x10 m.




Class	Max. Voltage use	Sticker Color
0	1000 V.	Red
2	17.000 V.	Yellow
3	26.500 V.	Green
4	36.000 V.	Orange




Antislip surface


CLASS 0




CLASS 2



CLASS 3



CLASS 4



CODE	CLASS	DIMENSIONS [m.]	WEIGHT [Kg.]	THICKNESS [mm.]	PROOF VOLTAGE [kVAC.]	WITHSTAND VOLTAGE [kVAC.]	RECOMMENDED MAX WORKING VOLTAGE [kVAC.]
BTIC011	0	1,0 x 1,0	3,4	3,0	5,0	10,0	1,0
BTIR010		10,0 x 1,0	34,0				
BTIC021	2	1,0 x 1,0	3,4	3,0	20,0	30,0	17,0
BTIR0210		10,0 x 1,0	34,0				
BTIC031	3	1,0 x 1,0	4,6	3,0	30,0	40,0	26,5
BTIR0310		10,0 x 1,0	46,0				
BTIC041	4	1,0 x 1,0	6,1	4,0	40,0	50,0	36,0
BTIR0410		10,0 x 1,0	61,0				



TYRSCO S.A. – 25 de Mayo 2666, El Talar (1618), Buenos Aires, Argentina. “LA SEGURIDAD NO ES CUESTION DE SUERTE”
 (+5411) 3221-0729, 4736-7531 - tyrco@tyrco.com.ar - www.tyrco.com.ar